



alveni.com

TB SERIES



KIOSK TB SERIES



Features

The standard basic kiosk has the following features:

- All metal 16 gauge powder-coated steel.
- 1/4" thick metal Base plate.
- VESA monitor mounting.
- 32" multitouch touchscreen monitor with up to 10 simultaneous touch points.
- PC Industrial Small Form Factor.
- Contemporary design.
- All-metal enclosure.
- Custom graphics available upon request.
- ADA compliant.
- Preparation in base to anchor to ground.

This kiosk is ideal for:



Schools and universities.



Client services.



Directory location.



Product information.



Virtual maps.



Tourist information.



Multuser interactive games.

Specifications

- **Material**
Powder-coated steel.
- **Finishing**
Powder coated paint.
- **Monitor**
32" anti-vandal SAW touchscreen multitouch.
- **CPU**
Industrial grade 4GB RAM, 250 DD, WinPOS Ready 7, Intel core i3, 84 W.
- **Energy requirements**
110 V.
- **Safety**
Rear door access with security camlock.
- **Table weight**
Enclosure: 100 lbs.
With components: 143 lbs. (approx.)
- **Temperature**
42 - 113° F (6-45 °C), for storage:
30 - 131 °F (0 - 55 °C).

Options

- **Colors**
Basic or premium color options.
- **Printer**
80mm.
- **Peripherals**
Barcode reader, fingerprint reader, speakers, magnetic stripe reader, webcam, hybrid reader and many others (call for other options).
- **Sensors**
Temperature, humidity, proximity.
- **CPU**
2nd gen. Core i3, i5 and GSeries processors, 2.5 inch rotating drive options from 320GB to 1TB, 2.5 inch Solid State Drive options from 8GB to 64GB and 2 to 8 RAM available.
- **OS**
Win POSReady 7, Windows 7 Pro (32 and 64 bit), Linux. (Call for version of interest).
- **Monitor**
32", 42", 55" or 70" multitouch touchscreen monitor with up to 10 simultaneous touch points.
- **Enclosure options**
Stainless steel, aluminum or powder-coated steel.
- **Graphics**
Custom graphics available upon request.
- **Brochure racks**
Optional racks mounted on the sides of the kiosk for applications, brochures or collateral.
- **Monitoring and application lock down**
Software platform for remote monitoring, session control, security and content update.
- **Warranty**
1 year standard, can be extended to 3 years.



*Design and measures may change according to the product updates.